

PVI 5000-F

- Integrated MPPT charge controller.
- Equalization charging function.
- Work with or without battery
- PV input voltage up to 450VDC.
- Configurable grid or solar input priority.
- Optional WIFI/GPRS remote monitoring
- Support parallel operation for capacity expansion up to 30kW.
- PV and grid power the load jointly if PV energy is insufficient.
- Flexibly schedule the Inverter charging and discharging time.



P O W E R
- I N G
T O M O R -
R R O W



www.powtran.com

Datasheet	PVI3000-F	PVI3500-F	PVI5000-F
Battery Voltage	48VDC		
Battery Type	Lithium/Lead-acid		
Inverter Output			
Rated Power	3000VA/ 3000W	3500VA/ 3500W	5000VA/ 5000W
Parallel Capability	NO	Yes, 6 units maximum	
AC Voltage Regulation (Battery Mode)	230VAC \pm 5% @ 50/60Hz		
Surge Power	60000VA	7000VA	10000VA
Efficiency (Peak)	93%		
Waveform	Pure sine wave		
Transfer Time	10ms typical, 20ms Max		
Solar Charger			
Maximum PV Array Power	4000W	4500W	6000W
MPPT Range @ Operating Voltage	120VDC ~ 430VDC		
Number of Independent MPP Trackers/ Strings Per MPP Tracker	1/1		
Maximum PV Array Open Circuit Voltage	450VDC		
Maximum Solar Charge Current	60A	80A	100A
AC Charger			
Charge Current	60A		80A
AC Input Voltage	230 VAC		
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)		
Frequency Range	50Hz/60Hz (Auto sensing)		
Physical			
Protection Degree	IP20		
Dimension (W/H/D)	330/485/135mm		
Net Weight	11.5kg	11.5kg	12kg
Operating Environment			
Humidity	5% to 95% Relative Humidity(Non-condensing)		
Altitude	<2000m		
Operating Temperature	0°C - 55°C		
Storage Temperature	-15°C - 60°C		

DALIAN POWTRAN TECHNOLOGY CO., LTD.
GUANGDONG POWTRAN POWER ELECTRONICS CO., LTD.

DALIAN OFFICE: No.11, Renxian Street, Qixianling, Hitech Industrial Zone, Dalian, Liaoning Province, P.R.C (116023)
DONGGUAN FACTORY: Building , No. 179, Fenggang Section, Dongshen Road Fenggang Town, Dongguan city, Guangdong, P.R.China 523681 Tel: +86 0769-22222279 Email: info@powtran.com http://www.powtran.com

